

Stainless Steel Threaded IMC

Features:

- Manufactured in type 304 & 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- No special tools required for installation
- Standard NPT threads allow for trouble-free installation
- Lighter weight provides cost savings with labor & shipping
- Includes one coupling with each length purchased
- Any custom size available up to 20' in length




Certifications and Compliances:

- UL and CUL 1242A / ANSI approved
- UL file number – E363502
- Full NEC code compliance
- Manufactured in the US

Applications:

Stainless steel IMC is often specified in corrosive environments where it is subjected to harsh chemical treatments or wash-downs due to its lighter weight, precise tolerances, and ease of installation.

Calbrite's IMC is manufactured with or without threads. The threaded conduit can be used with compression or standard threaded couplings, allowing for lowered costs and simplified installations.



Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical
- Pulp & Paper Mills
- Marine & Coastal Facilities
- Along with other corrosive environments

Trade Size	Metric Size	OD	ID	Wt./Ft. (lbs)	Type 304 Part Number	Type 316 Part Number
1/2"	16	0.815"	0.660"	0.62	S50510CTWT	S70510CTWT
3/4"	21	1.029"	0.864"	0.84	S50710CTWT	S70710CTWT
1"	27	1.290"	1.120"	1.19	S51010CTWT	S71010CTWT
1-1/2"	41	1.883"	1.703"	1.94	S51510CTWT	S71510CTWT
2"	53	2.360"	2.170"	2.56	S52010CTWT	S72010CTWT

*All dimensions are for informational purposes only *Tolerances +/- 5%*