

Calbrite™

Stainless Steel Conduit Systems

Stainless Steel FDCC and FSCC Single Gang Device Boxes

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined standard NPT threads
- Internal grounding screw included
- Manufactured with mounting feet
- No package qty. required



Certifications and Compliances:

UL514A approved – file # E307133

Material: Body - CF8M (316)

Grounding Screws: 316SS

Standards: ASTM A351

Applications:

Used for wiring devices, such as switches and receptacles

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments



Size	Part Number	Overall Length	Overall Width	Depth	Cubic In.	Center Hole to Center Hole	Mounting Feet Hole Dia.	Weight (ea) per lb.
3/4"	S60700FDCC	5.900"	2.835"	2.500"	25"	3.300"	5/16"	2.50
3/4"	S60700FSCC	5.900"	2.835"	1.800"	18"	3.300"	5/16"	2.10

*All dimensions are for informational purposes only * Tolerances +/- 5%*