

Stainless Steel FDC Double Gang Device Boxes

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Machined standard NPT threads
- Internal grounding screw included
- Manufactured with mounting feet
- No package qty. required
- Ports located on top & bottom

Certifications and Compliances:

UL514A approved—file # E307133
 Material: Body—CF8M (316)
 Grounding Screws: 316SS

Applications:

Used for wiring devices, such as switches and receptacles

Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp & Paper Mills
- Along with other corrosive environments



Size	Part Number	Overall Length	Overall Width	Depth	Cubic In.	Center Hole to Center Hole	Mounting Feet Hole Diameter	Weight (ea) per lb.
3/4"	S60700FDCCD	6.000"	4.670"	2.500"	45"	3.300"	5/16"	3.57
1"	S61000FDCCD	6.320"	4.670"	2.500"	45"	3.300"	5/16"	3.95

*All dimensions are for informational purposes only *Tolerances +/- 5%*