



30W/LED/HID/MB/5000K/100-277V E26

30 watt - LED HID Replacement; 5000K; Medium base; 100-277 volts

Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

Width (360°)	Width (270°)	Width (180°)
3.2"	6.8"	7.7"

Minimum lamp compartment dimensions: 203mm x 203mm x 280mm (7.99" x 7.99" x 11.02")

Item S9750

Product Line	Hi-Pro
UPC	045923097508
Input Voltage	100 - 277
Watts	30
Incandescent Equivalent	200W
Fluorescent Equivalent	55W
HID Equivalent	150W
Power Factor	0.90
Base	Medium
ANSI Base	E26
Lamp Code	30W/LED/HID/MB/5000K/100-277V E26
Dimmable/Non-Dimmable	Non-Dimmable
Finish	White
MOL In Inches	6-3/8"
MOD In Inches	3-3/16" (Open 7-11/16")
Initial Lumens	3900
Average Rated Hours	50000
Kelvin Temp	5000
Color	Natural Light
CRI	80+
Beam Spread Deg	Adjustable: 360; 270; 180
Operating Temperature	-20C (-4F) to a maximum of +65 (+149F)
Pack	24/6
Package Type	Box
RoHS Compliant	Yes
Fixture Type	Enclosed Rated
UL or ETL Listed	Yes
UL Classification	cULus - Damp Location Rated
Warranty	5 Year Limited