



60W/LED/HID/MB/5000K/100-277V

60 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

Features

- Replaces HID, CFL, and Incandescent
- Direct wire range voltage 100-277V
- Approved for totally enclosed fixtures
- Hi bay, low bay and post top
- Light panels lock into place creating 3 separate beam angle options
- IP65 rated
- DLC Qualified
- 5 year limited warranty

Specification note: Power Factor >0.9; Operating temperature range -20°C to 65°C; Operating Frequency 50-60Hz; Working Voltage AC 90-305V

Optional accessory: In-line surge protector [80-929](#)

Width (360°)	Width (270°)	Width (180°)
3.8"	8.2"	9.3"

Minimum lamp compartment dimensions: 235mm x 235mm x 210mm (9.25" x 9.25" x 8.27")

Item S9752

Product Line	Hi-Pro
UPC	045923097522
Input Voltage	100 - 277
Watts	60
Incandescent Equivalent	500W
Fluorescent Equivalent	85W
HID Equivalent	250W
Power Factor	0.90
Base	Mogul Extended
ANSI Base	EX39
Lamp Code	60W/LED/HID/MB/5000K/100-277V
Dimmable/Non-Dimmable	Non-Dimmable
Finish	White
MOL In Inches	8-9/16"
MOD In Inches	3-13/16" (Open 9-5/16")
Initial Lumens	7800
Average Rated Hours	50000
Kelvin Temp	5000
Color	Natural Light
CRI	80+
Beam Spread Deg	Adjustable: 360; 270; 180
Operating Temperature	-20C (-4F) to a maximum of +65C (+149F)
Pack	12/6
Package Type	Box
DLC ID:	PZY8T15P DLC Search
RoHS Compliant	Yes
Fixture Type	Enclosed Rated
UL or ETL Listed	Yes
UL Classification	cULus - Damp Location Rated
Warranty	5 Year Limited

EMAIL 

SPECIFICATIONS SHEET

