

# TURCK M8 picofast® Connectivity

## 3 and 4-Wire Field Wireable Connectors, Standard

- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>B 513(4)1-0</b></p>	<b>B 5131-0</b>	<b>BS 5131-0</b>	PBT, Black, accepts 3-5 mm cable diameter, solder terminals, accepts up to 24 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 3-pin threaded cordsets and receptacles	<p><b>Female</b></p> <p><b>Male</b></p>
<p><b>BS 513(4)1-0</b></p>	<b>B 5141-0</b>	<b>BS 5141-0</b>	PBT, Black, accepts 3-5 mm cable diameter, solder terminals, accepts up to 24 AWG conductors, 85°C, 30 VAC/ 36 VDC, 4.0 A, mates with 4-pin threaded cordsets and receptacles	<p><b>Female</b></p> <p><b>Male</b></p>
<p><b>B 513(4)3-0</b></p>	<b>B 5133-0</b>	<b>BS 5133-0</b>	PBT, Black, accepts 3-5 mm cable diameter, screw terminals, accepts up to 22 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 3-pin threaded cordsets and receptacles	<p><b>Female</b></p> <p><b>Male</b></p>
<p><b>BS 513(4)3-0</b></p>	<b>B 5143-0</b>	<b>BS 5143-0</b>	PBT, Black, accepts 3-5 mm cable diameter, screw terminals, accepts up to 22 AWG conductors, 85°C, 60 VAC/ 75 VDC, 4 A, mates with 4-pin threaded cordsets and receptacles	<p><b>Female</b></p> <p><b>Male</b></p>