

# Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
<b>18 mm - Embeddable, eurofast® Connection, PTFE Coated</b>  	Bi 7-MT18H-AD4X-H1141	T4414580-1	Extended Range	7	2-Wire DC
	Bi 5U-MT18-AN6X-H1141	M1635250	<b>Uprox</b>	5	3-Wire DC NPN
	Bi 8U-MT18-AN6X-H1141	M1644739	<b>Uprox+</b> PTFE	8	
	Bi 8U-MT18-AN6X-H1141/S1589	M1644791	<b>Uprox+</b> PTFE, weldguard	8	
	Bi 5U-MT18-AP6X-H1141	M1635240	<b>Uprox</b>	5	3-Wire DC PNP
	Bi 5U-MT18-AP6X2-H1141	M1635245	<b>Uprox</b>	5	
	Bi 8U-MT18-AP6X-H1141	M1644730	<b>Uprox+</b> PTFE PTFE, weldguard	8	
<b>18 mm - Embeddable, eurofast Connection, Short Barrel</b>  	Bi 8-M18K-AP6X-H1141	T4615050	Ext. Range, Short Barrel	8	3-Wire DC PNP

For detailed sensor specifications see Section M.  
Normally Closed versions available upon request, consult factory.