

2-Wire Cordsets, Standard Plug Body



- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>RK..**</p>	RK 4.2T-* WK 4.2T-*	RS 4.2T-* WS 4.2T-*	AWM PVC Grey, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF50529-*M [†] , flexlife [†]	<p>Female</p> <p>Male</p>
<p>WK..**</p>	RK 4.2T-*/S90 WK 4.2T-*/S90	RS 4.2T-*/S90 WS 4.2T-*/S90	AWM TPU Grey, 2x20 AWG, 90°C, 4.8 mm OD, Cable #RF50772-*M [†] , Cut/Abrasion Immune, tray rated	
<p>RS..**</p>	RK 4.2T-*/S748 WK 4.2T-*/S748	RS 4.2T-*/S748 WS 4.2T-*/S748	AWM PVC Yellow, 2x22 AWG, 105°C, 5.1 mm OD, Cable #RF50650-*M [†] , flexlife	
<p>WS..**</p>	RK 4.21T-*/S1511 WK 4.21T-*/S1511	RS 4.21T-*/S1511 WS 4.21T-*/S1511	AWM PVC Grey, 2x20 AWM PVC, 105°C, 5.1 mm OD, Cable #RF50529-*M [†]	
	RK 4.21T-* WK 4.21T-*	RS 4.21T-* WS 4.21T-*	AWM PVC NAMUR Blue, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF20003-*M [†]	
	RK 4.21T-*/S90 WK 4.21T-*/S90	RS 4.21T-*/S90 WS 4.21T-*/S90	AWM TPU NAMUR Blue, 2x20 AWG, 90°C, 5.1 mm OD, Cable #RF50657-*M [†] , Cut/Abrasion Immune	
	RK 4.22T-* WK 4.22T-*	RS 4.22T-* WS 4.22T-*	AWM PVC Grey, 2x20 AWG, 105°C, 5.1 mm OD, Cable #RF50529-*M [†] , flexlife	
	RK 4.23T-* WK 4.23T-*	RS 4.23T-* WS 4.23T-*		

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RK .."; "RKK .." indicates nylon and "RKK .." indicates stainless steel.
 † See Section N for **reelfast**® cable information.