


Flexible Control Cables

CC 600 CY

Oil Resistant 90°C flexible shielded control cable



600V Oil 60°C CSA AWM I/II A/B 90°C F 600V FT1 FT2 CE



A
6

Marking for CC 600 CY 02591804:
SAB BRÖCKSKES · D-VIERSEN · <VDE-REG 7000> 4x1.0mm² CC 600 CY 18 AWG/4c 02591804
AWM Style 21216 90°C 600V Oil 60°C CSA AWM I/II A/B 90°C F 600V FT1 FT2 CE

Construction:

Conductor: AWG 20 - 10:	bare copper strands acc. to IEC 60228, VDE 0295, class 5
AWG 8 - 1:	bare copper strands acc. to UL/CSA
Insulation:	special PVC acc. to VDE and UL/CSA
Color code:	black conductors with consecutive numbers acc. to EN 50334 + VDE 0293-334, green/yellow ground from 3 conductors
Stranding:	in layers
Inner Jacket:	special PVC acc. to VDE and UL/CSA
Shielding:	tinned copper braiding
Jacket material:	special oil resistant PVC acc. to VDE and UL/CSA
Jacket color:	gray (RAL 7000)

Technical data:

Nominal voltage:	Uo/U 300/500 V	
Voltage UL/CSA:	600 V	
Testing voltage:	conductor/conductor:	3000 V
	conductor/shielding:	2000 V
Min. bending radius:		
fixed installation:	5 x O.D.	
free movement:	10 x O.D.	
Radiation resistance:	5 x 10 ⁷ cJ/kg	
Temperature range:	DIN VDE	UL/CSA: up to +90°C
static:	-40/+70°C	
flexible:	+5/+70°C	
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1-2 + VDE 0482-332-1-2, UL VW-1, CSA FT1, FT2	
Oil resistance:	very good - PVC, TM5 acc. to DIN VDE 0281 part 1 + HD 21.1, Oil 60°C acc. to UL 758, Fuel Oil acc. to CSA-C 22.2 No. 210	
Chemical resistance:	see page O/11	
Approvals:	UR AWM, CSA AWM, CE, EAC, RoHS	
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30	

Outstanding features:



- UL recognized, CSA approved
- high mechanical loading capacity
- oil resistant
- AWG 20 - AWG 10:
built acc. to VDE-Reg. no. 7000
- good EMC characteristics

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 20 AWG (≈ 16/32) ▪ 0.50 mm²				
02592002	2	0.291	7.4	55
02592003	3	0.311	7.9	64
02592004	4	0.331	8.4	73
02592005	5	0.358	9.1	85
02592007	7	0.378	9.6	98
02592010	10	0.469	11.9	148
02592012	12	0.492	12.5	163
02592025	25	0.657	16.7	288
▶ 18 AWG (≈ 30/32) ▪ 1.0 mm²				
02591802	2	0.327	8.3	71
02591803	3	0.339	8.6	79
02591804	4	0.370	9.4	95
02591805	5	0.402	10.2	117
02591807	7	0.437	11.1	140
02591809	9	0.535	13.6	195
02591812	12	0.555	14.1	218
02591818	18	0.642	16.3	310
02591825	25	0.772	19.6	411

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 16 AWG (≈ 27-29/30) ▪ 1.50 mm²				
02591602	2	0.358	9.1	87
02591603	3	0.374	9.5	98
02591604	4	0.406	10.3	122
02591605	5	0.433	11.0	144
02591607	7	0.480	12.2	176
02591612	12	0.614	15.6	274
02591618	18	0.724	18.4	394
02591625	25	0.878	22.3	548
▶ 14 AWG (≈ 46/30) ▪ 2.50 mm²				
02591403	3	0.441	11.2	144
02591404	4	0.476	12.1	172
02591405	5	0.520	13.2	206
02591407	7	0.567	14.4	256
02591412	12	0.744	18.9	418
02591418	18	0.874	22.2	585
02591425	25	1.028	26.1	773

item no.	no. of conductors incl. ground	nominal outer-ø inch	mm	cable weight ≈lbs/mft
▶ 12 AWG (≈ 52/28) ▪ 4.00 mm²				
02591203	3	0.512	13.0	201
02591204	4	0.555	14.1	243
02591205	5	0.602	15.3	285
02591207	7	0.665	16.9	372
▶ 10 AWG (≈ 78/28) ▪ 6.00 mm²				
02591003	3	0.587	14.9	273
02591004	4	0.630	16.0	323
02591005	5	0.705	17.9	406
02591007	7	0.772	19.6	511
▶ 8 AWG (≈ 69/26)				
02590804	4	0.807	20.5	531
▶ 6 AWG (≈ 110/26)				
02590604	4	0.957	24.3	746
▶ 4 AWG (≈ 175/26)				
02590404	4	1.157	29.4	1144
▶ 2 AWG (≈ 272/26)				
02590204	4	1.346	34.2	1564
▶ 1 AWG (≈ 342/26)				
02590104	4	1.441	36.6	1882

Other dimensions and colors are available on request



also available with blue, red or orange conductors and black or orange jacket