

## 4-Wire Receptacles, Front Mount, 1/2-14 NPSM Threads

- EMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>RKF ..</b></p> <p>Typical panel cutout 22.5 mm</p>	RKF 40-*M	RSF 40-*M	4x18 AWG 105°C, 600 V, 9 A, standard duty	<p><b>Female</b></p>
		RSF 40-*M/S658	4x18 AWG, 105°C, 300 V, 9 A, standard duty	<p>1. BN 2. WH 3. BU 4. BK</p> <p><b>Male</b></p>
	RKF 40-*M/S849	RSF 40-*M/S849	4x22 AWG, 105°C, 300 V, 5 A, standard duty	
<p><b>RSF ..</b></p> <p>Typical panel cutout is 22.5 mm</p>	RKF 46-*M	RSF 46-*M	4x16 AWG, 105°C, 600 V, 10 A, heavy duty	<p><b>Female</b></p>
		RKF 46-*M/S849	RSF 46-*M/S849	4x22 AWG, 105°C, 300 V, 5 A, heavy duty
	RKF 48-*M	RSF 48-*M	4x18 AWG, 105°C, 600 V, 9 A, standard duty	<p>1. BN 2. N/C 3. BU 4. N/C</p> <p><b>Female</b></p> <p><b>Male</b></p>

Standard lead length is 0.3 Meters. Consult factory for other lengths.

\*\* Standard housing material is nickel plated brass. "RSF .."; "RSFV .." indicates stainless steel housing, and "RSFK .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.