
## A19-10-9CCT-DIM



## **Technical Specifications**

#### Performance

Product Type: A-Line

Description:

CCT-selectable lamps replace up to 100W conventional incandescent.

Wattage Equivalency:

75W Incandescent

Input Wattage: 10W

#### Lumens:

1,124lm @ 2700K 1,187lm @ 3000K 1,268lm @ 3500K 1,273lm @ 4000K 1,174lm @ 5000K

### Efficacy:

117lm/W @ 2700K 122lm/W @ 3000K 127lm/W @ 3500K 127lm/W @ 4000K 121lm/W @ 5000K L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results

Electrical Power Factor:

>0.7

Dimmable: Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems. See Dimmer Compatibility List.

Input Voltage: 120V

Operating Frequency: 60 Hz

Input Current @ 120V (mA): 115mA

**Operating Temperature:** -4°F to 113°F (-20°C to 45°C)

**Flicker:** <30%

## **LED Characteristics**

Beam Angle: 160°

**Color Temperature:** Field adjustable via dip switch 2700/3000/3500/4000/5000K Default setting: 3000K

Color Accuracy (CRI): ≥90

**R9 Value:** High color performance with R9 no greater than 0

Color Consistency: <4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Installation

Base Type: E26 Edison

Construction Bulb Shape: A19

## A19-10-9CCT-DIM

# RAB

## **Technical Specifications (continued)**

Finish: White

Endcap Material:

Aluminum

Lens Finish: Frosted

Compliance Listings: UL Listed

**Environment:** Suitable for use indoors in dry and damp environments.

**Fixture Rating:** Suitable for use in enclosed fixtures

Energy Star Approved: No

**Certification Model Number:** A10123(A19-10-9CCT-DIM)

### California Title 20 Compliant:

Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant: No

California Energy Commission (CEC) Status:

Lawful for Sales in California

### **RoHS:**

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules

### Other

/

### 3-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>

## A19-10-9CCT-DIM

## **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	10.83	8.15	10.24
PALLET	2	48.9	37.96	51.2
		1	1	I

## Dimension

