

Data Sheet | Item Number: 221-683


Splicing connector with levers; for all conductor types; for Ex e applications; max. 6 mm²; 3-conductor; transparent housing; Operating temperature (max.): 105 °C; 6,00 mm²; transparent

<https://www.wago.com/221-683>



Color: ☐ transparent





Dimensions in mm

Splicing connector with levers, 221 Series, CAGE CLAMP®

Splicing connector with levers (item number 221-683) simplifies electrical installations. From wiring intercom systems to installing electrical ovens, connecting different conductor types is quick and hassle-free with WAGO's compact 221 Series splicing connector, which allows you to quickly and safely connect different types of conductors. Strip lengths must be between 12 mm and 14 mm when connecting conductors to splicing connector with levers. This product features conductor terminals and utilizes CAGE CLAMP®. Our trusted universal connection known as CAGE CLAMP® is the industry standard when it comes to connection technology and electrical interconnections. The dimensions are 22.9 x 10.1 x 21.1 mm (width x height x depth). Depending on the type of conductor, splicing connector with levers is designed for conductor cross sections ranging from 0.5 mm² to 6 mm².

WAGO's 221 Series Splicing Connector with levers impresses with its innovative design for different conductor cross-sections. That's why WAGO's lever-equipped splicing connector holds a unique trademark within electrical interconnection technology. The flat levers, which fit seamlessly into the 221's base, act like a cast when closed and can be positioned neatly in any housing without disturbing edges. Due to the wide design of each lever, they can all be operated perfectly without tools for convenient conductor terminations. The transparent housing displays robust technology and enables immediate visual inspection for the correct contact of solid, stranded and fine-stranded conductors. Resembling piano keys, the levers' design perfectly combines the functional and aesthetic connection technology "Made by WAGO." This product is designed for specific Ex applications (please refer to the product datasheet).

Notes	
General safety instructions	<div>NOTICE: Observe installation and safety instructions!</div> <div><ul style="list-style-type: none">• Only to be used by electricians!• Do not work under voltage/load!• Use only for proper use!• Observe national regulations/standards/guidelines!• Observe technical specifications for the products!• Observe the number of permissible potentials!• Do not use damaged/dirty components!• Observe conductor types, cross-sections and strip lengths!• Insert conductor until it hits the product's backstop!• Use original accessories!</div> <div>To be sold only with installation instructions!</div>
Safety Information	The permissible operating voltage of the connector with carrier (440 V or 275 V) depends on the mounting type.
Safety information 2	<div>Only approved in conjunction with a mounting carrier (221-511). Other carriers are possible, see certificate/file.</div> <div>The connectors must be installed in an enclosure meeting the requirements of a recognized protection type per EN 60079-0, Section 1 or EN 60079-31.</div> <div>When installing the connectors in an enclosure of protection type "eb" (increased safety) per EN 60079-7, the clearances and creepage distances of Table 2 for this standard must be observed. See point 1 for the use of accessories. The connectors can be used both in Group II and Group I, as the standard requirements are identical in this case.</div> <div>The use of these components requires a new assessment by a notified certification agency.</div>



Electrical data				
Approvals per		UL 60079		
Use group	B	C	D	
Rated voltage	-	440 V	-	
Rated current	-	30 A	-	

Ex information	
Ratings per	ATEX: PTB 19 ATEX 1001 U / IECEx: PTB 19.001 1U (Ex eb IIC Gb)
Rated voltage EN (Ex e II)	440 V
Rated current (Ex e II)	37 A

Connection data	
Clamping units	3
Total number of potentials	1

Connection 1	
Connection technology	CAGE CLAMP®
Actuation type	Lever
Connectable conductor materials	Copper
Nominal cross-section	6 mm² / 10 AWG
Solid conductor	0.5 ... 6 mm² / 20 ... 10 AWG
Stranded conductor	0.5 ... 6 mm² / 20 ... 10 AWG
Fine-stranded conductor	0.5 ... 6 mm² / 20 ... 10 AWG
Strip length	12 ... 14 mm / 0.47 ... 0.55 inches
Wiring direction	Side-entry wiring

Physical data	
Width	22.9 mm / 0.902 inches
Height	10.1 mm / 0.398 inches
Depth	21.1 mm / 0.831 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	transparent
Material group	Illa
Insulation material (main housing)	Polycarbonate (PC)
Flammability class per UL94	V2
Fire load	0.097 MJ
Actuator color	light gray
Weight	4.3 g

Environmental requirements	
Ambient temperature (storage)	-40 ... +60 °C
Continuous operating temperature	-55 ... +105 °C



Commercial data	
PU (SPU)	300 (30) pcs
Packaging type	Box
Country of origin	DE
GTIN	4055143860574
Customs tariff number	85369010000



Product classification	
UNSPSC	39121409
ETIM 9.0	EC000446
ETIM 8.0	EC000446
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals		Declarations of conformity and manufacturer's declarations
 		
Approval	Standard	Certificate Name
CB DEKRA Certification B.V.	IEC 60998	NL-114612
cULus_Listed_667F Underwriters Laboratories Inc.	UL 486C	E69654
ENEC 05 DEKRA Certification B.V.	EN 60998	71-152265
		ATEX-Attestation of Con- formity WAGO GmbH & Co. KG
		EU-Declaration of Confor- mity WAGO GmbH & Co. KG
		UK-Declaration of Confor- mity WAGO GmbH & Co. KG

Approvals for marine applications		Approvals for hazardous areas
		    
Approval	Standard	Certificate Name
LR Lloyds Register	EN 60998	LR22207029TA
		AEx Underwriters Laboratories Inc.
		ATEX Physikalisch Technische Bundesanstalt
		CCC CNEX
		IECEX Physikalisch Technische Bundesanstalt
		INMETRO TÜV Rheinland do Brasil Ltda.
		UL 60079
		EN IEC 60079-0
		GB/T 3836.3
		IEC 60079-0
		IEC 60079
		PTB 19 ATEX 1001 U (II 2 G Ex eb IIC Gb, I M 2 Ex eb I Mb)
		2020312313000185 (Ex eb IIC Gb, Ex eb I Mb)
		IECEX PTB 19.001 1U (EX eb IIC Gb, Ex eb I Mb)
		TÜV 19.1781 U



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 221-683

↓

Documentation

Bid Text

ausschreiben.de
221-683

↓

CAD/CAE-Data

CAD data

2D/3D Models 221-683

↓

CAE data

EPLAN Data Portal 221-683

↓

ZUKEN Portal 221-683

↓

1 Compatible Products

1.1 Optional Accessories

1.1.1 Mounting adapter

1.1.1.1 Mounting accessories




Item No.: 221-510/000-006
Mounting carrier; 221 Series - 6 mm²; for DIN-35 rail mounting/screw mounting; blue


Item No.: 221-511
Mounting carrier; for Ex applications; 221 Series - 6 mm²; for DIN-35 rail mounting/screw mounting; light gray

Installation Notes


Conductor termination



Strip conductor to 11 mm (0.43 inch).



Then, lower the lever to close the clamp.



Termination: Lift the lever to open the clamping unit and insert a stripped conductor.

Installation



Inserting a connector into the mounting carrier.



Removing a connector from the mounting carrier.



Removing a conductor.



Mounting type (440 V)
Using spacers between the connectors.



Mounting type (440 V)
Vertical mounting on DIN-35 rail



Mounting type (440 V)
Horizontal screw mounting on a flat surface



Mounting type (440 V)
Mounting the carrier via non-conductive screws.



Mounting type (275 V)
No spacers are used between the connectors.



Mounting type (275 V)
Mounting the carrier using conductive screws.

Testing



Easily test inserted connectors in the carrier – however they are mounted.