

Antenna - RAD-ISM-900-ANT-YAGI-3-N - 2867801

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Panel antenna, IP65 protection, gain 5 dBi, cable length 0.6 m, connection N (female)



Product Features

- Longer ranges than omnidirectional antennas
- Stationary applications
- Point-to-point configurations with line of sight

Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	1150.0 g
Country of origin	United States

Technical data

Dimensions

Width	6 cm
Height	17 cm
Fixed cable length	0.60 m

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 80 °C

General

With connecting cable	yes
Frequency range	900 MHz
	900 MHz
Horizontal beamwidth	168 °
Vertical beamwidth	78 °
Impedance	50 Ω
Gain	5 dBi

Antenna - RAD-ISM-900-ANT-YAGI-3-N - 2867801

Technical data

General

Wind velocity	200 km/h
Connection method	N (female) with cable (0.6 m)
Fixed cable length	0.60 m

Classifications

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	19070102
eCl@ss 5.1	19070102
eCl@ss 6.0	19070102
eCl@ss 7.0	19070102
eCl@ss 8.0	19070105
eCl@ss 9.0	19070105

ETIM

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706