

DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail connector for DIN rail mounting. Universal for TBUS housing. Gold-plated contacts, 5-pos.



Product Features

- For bridging the supply voltage
- One DIN rail connector for two MINI Analog modules
- Current carrying capacity of 8 A parallel to DIN rail and 2 A parallel to MINI Analog modules
- Reduced wiring effort
- Module replacement without interrupting the supply to the remaining modules (hot swappable)



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	6.24 g
Country of origin	Germany

Technical data

Width	6.2 mm
Number of positions	5

General

Color	green
-------	-------

Dimensions

Width	6.2 mm
Pitch	3.81 mm

Technical data

DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

Technical data

Technical data

Connection in acc. with standard	CUL
Nominal voltage U_N	150 V
Nominal current I_N	8 A
Indicator1	CUL1
Number of positions	5

Standards and Regulations

Connection in acc. with standard	CUL
----------------------------------	-----

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC002638
ETIM 5.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

DIN rail connector - ME 6,2 TBUS-2 1,5/5-ST-3,81 GN - 2869728

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	150 V	150 V

cUL Recognized		
	B	D
Nominal current I _N	8 A	8 A
Nominal voltage U _N	150 V	150 V

EAC

EAC

cULus Recognized
