


Isolating plugs - ST-K 4 - 5025462

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Isolating connector, can be used in UK...-TG, UKK...-TG, UDK...-TG, MBK...-TG, DIK...-TG, DOK...-TG, and ZFK...-TG disconnect terminal blocks, color: gray

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 095321
Weight per Piece (excluding packing)	1.74 g
Country of origin	Germany

Technical data

General

Number of positions	1
Color	gray
Insulating material	PA
Flammability rating according to UL 94	V2

Dimensions

Width	4.5 mm
Length	10 mm
Height	31.2 mm
Pitch	4.5 mm

General

Nominal current I_N	16 A
Nominal voltage U_N	400 V

Connection data

Connection method	Plug connection
-------------------	-----------------

Isolating plugs - ST-K 4 - 5025462

Technical data

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002497
ETIM 5.0	EC000489

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Isolating plugs - ST-K 4 - 5025462

Approvals

Approvals submitted

Approval details

EAC

EAC

Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block



Universal tools

Plug extraction tool - TZ - 0306704



Connector pliers, simplify removing the isolating connector from a closed row of terminal blocks (if installed individually)
