

## Socket - EMG 30-SD/US/15A - 5604253

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Rail-mounted single receptacle for mounting on 35 mm DIN rail per EN 60715. Housing color: black. Receptacle style: USA. Connection type: screw.

### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	59.6 g
Country of origin	United States

### Technical data

#### Dimensions

Width	30 mm
Height	75 mm
Depth	54 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

#### General

Nominal voltage $U_N$	120 V AC
Nominal current $I_N$	15 A
For country-specific use in	USA
	Canada
	China
	Japan
	Mexico
	Peru
	Saudi Arabia
	Taiwan
	Thailand
	Phillipines
	Venezuela
	Vietnam
Color	black
Insulating material	PVC 94 V0

#### Connection data

# Socket - EMG 30-SD/US/15A - 5604253

## Technical data

### Connection data

Conductor cross section AWG min.	30
Conductor cross section AWG max.	12
Connection method	Screw connection

## Classifications

### eCl@ss

eCl@ss 4.0	27142305
eCl@ss 4.1	27142305
eCl@ss 5.0	27143412
eCl@ss 5.1	27143412
eCl@ss 6.0	27143412
eCl@ss 7.0	27440519
eCl@ss 8.0	27142305

### ETIM

ETIM 3.0	EC001325
ETIM 4.0	EC001663
ETIM 5.0	EC001663

### UNSPSC

UNSPSC 6.01	30211806
UNSPSC 7.0901	39121406
UNSPSC 11	39121406
UNSPSC 12.01	39121406
UNSPSC 13.2	39121406

## Approvals

### Approvals

---

#### Approvals

UL Listed / cUL Listed / cULus Listed

---

#### Ex Approvals

---

## Socket - EMG 30-SD/US/15A - 5604253

### Approvals

Approvals submitted

---

#### Approval details

UL Listed	
mm <sup>2</sup> /AWG/kcmil	30-10
Nominal current I <sub>N</sub>	15 A
Nominal voltage U <sub>N</sub>	120 V

cUL Listed	
mm <sup>2</sup> /AWG/kcmil	30-10
Nominal current I <sub>N</sub>	15 A
Nominal voltage U <sub>N</sub>	120 V

