

# Calbrite™

## Stainless Steel Conduit Systems

### Stainless Steel Strut Clamps

#### Features:

- Manufactured in type 316 stainless steel to meet any stringent sanitary condition
- Polished with standard "brite" finish to increase corrosion resistance and aesthetic appearance
- Designed for use with 1-5/8" stainless channel
- No package qty. required
- Type 316 stainless steel nut & bolt included




#### Certifications and Compliances:

Calbrite stainless steel strut clamps are fabricated to UL and ASTM A167, F593 standards

#### Applications:

Used at any point along the slot side of the channel and are inserted into the two channel returns. Designed for use in standard 1-5/8" channels. Supplied with stainless nut and bolt.



#### Industries Commonly Served:

- Food & Beverage Production & Distribution
- Chemical Plants
- Water & Wastewater Treatment
- Pharmaceuticals & Cosmetics
- Refining & Extraction Sites
- Petrochemical Operations
- Marine & Coastal Facilities
- Pulp and Paper Mills
- Along with other corrosive environments

| Size   | Part Number | Material Thickness | Design Load (lbs.) | Bolt Size       | Weight per 100 (lbs.) |
|--------|-------------|--------------------|--------------------|-----------------|-----------------------|
| 1/2"   | S60500SC00  | 0.060"             | 400                | 1/4 -20 x 3/4"  | 11                    |
| 3/4"   | S60700SC00  | 0.060"             | 600                | 1/4 -20 x 3/4"  | 12                    |
| 1"     | S61000SC00  | 0.075"             | 600                | 1/4 -20 x 3/4"  | 16                    |
| 1-1/4" | S61200SC00  | 0.075"             | 600                | 1/4 -20 x 3/4"  | 18                    |
| 1-1/2" | S61500SC00  | 0.105"             | 800                | 5/16-18 x 1"    | 26                    |
| 2"     | S62000SC00  | 0.105"             | 800                | 5/16-18 x 1"    | 31                    |
| 2-1/2" | S62500SC00  | 0.105"             | 800                | 5/16-18 x 1"    | 35                    |
| 3"     | S63000SC00  | 0.105"             | 800                | 5/16-18 x 1"    | 41                    |
| 3-1/2" | S63500SC00  | 0.120"             | 1000               | 3/8-16 x 1-1/4" | 50                    |
| 4"     | S64000SC00  | 1.120"             | 1000               | 3/8-16 x 1-1/4" | 62                    |

*All dimensions are for informational purposes only \*Tolerances +/- 5%*