NSENSORS



Part Number	ID Number	Drawing
BIM-UNT, Potted-in cable, 2M and 7M		
BIM-UNT-AP6X	S4685720	1
BIM-UNT-AN6X	S4685702	1
BIM-UNT-AP6X 7M	S4685721	1
BIM-UNT-AN6X 7M	S4685701	1
BIM-UNT, M8 picofast® quick-disconne	ct pigtail, 0.3M PUR	cable
BIM-UNT-AP6X-0.3M-PSG 3S	S4685722	2
BIM-UNT-AN6X-0.3M-PSG 3S	S4685705	2
BIM-UNT, M8 picofast® threaded pigta	il, 0.3M PUR cable	
BIM-UNT-AP6X-0.3M-PSG 3M	S4685723	3
BIM-UNT-AN6X-0.3M-PSG 3M	S4685706	3
BIM-UNT, M12 eurofast® quick-disconn	ect pigtail, 0.3M PUI	R cable
BIM-UNT-AP6X-0.3M-RS 4T	S46857260	4
BIM-UNT Dually, M12 eurofast® thread	ed pigtail, 0.2M PUR	cable
BIM-UNT-2AP6X-0.2M-RSC 4.4T	S4685891	5
BIM-UNR, Potted-in cable, 2M and 7M	PUR cable	
BIM-UNR-AP6X W/M	S4685842	6
BIM-UNR-AN6X W/M	S4685847	6
BIM-UNR-AN6X 7M W/M	S4685851	6
BIM-UNR-AP6X 7M W/M	S4685846	6
BIM-UNR, M8 picofast® quick-disconne	ct pigtail, 0.3M PUR	cable
BIM-UNR-AP6X-0.3M-PSG 3S W/M	S4685843	7
BIM-UNR-AN6X-0.3M-PSG 3S W/M	S4685848	7
BIM-UNR, M8 picofast® threaded pigta	il, 0.3M PUR cable	
BIM-UNR-AP6X-0.3M-PSG 3M W/M	S4685844	8
BIM-UNR-AN6X-0.3M-PSG 3M W/M	S4685849	8
BIM-UNR, M12 eurofast® threaded pigt	ail, 0.3M PUR cable	
BIM-UNR-AP6X-0.3M-RS 4T W/M	S4685845	9
BIM-UNR-AN6X-0.3M-RS 4T W/M	S4685850	9
BIM-UNR Dually, M12 eurofast® quick-o	disconnect pigtail, 0.	2M PUR cable
BIM-UNR-2AP6X-0.2M-RSC 4.4T	S4685899	10

Dimensional Drawings	
1	6
.197 [5.0] LED 1.102 [28.0]	.114 [2.9] LED .181 [4.6]
2	7
.236 [6.0] .197 [5.0] LED LED 1,102 [28.0]	.114 [2.9] .181 [4.6] .181 [4.6]
3	8
.197 [5.0] LED 1.102 [28.0]	.114 [2.9] .181 [4.6] .709 [18.0]
4	9
.197 [5.0] LED	.114 [2.9] LED LED 709 [18.0]
5	10
.197 [5.0] LED 1.102 [28.0]	.114 [2.9] CLED 7.09 [18.0]

Technical Specifications:

Ambient Temperature:	-25° to +70°C (-13° to 158°F)
Operating Voltage:	10-30 VDC
Ripple V _{pp} :	≤ 10% U _{ss}
No-load Current I₀:	≤ 15 mA
Off-state Current:	≤ 0.1 mA
Switching Frequency:	UNT: ≤ 1 kHz; UNR: ≤ 0.3 kHz
Rated Operating Current:	UNT: DC ≤ 150 mA; UNR: DC ≤ 100 mA

3-wire, N.O., PNP/NPN Output Function:


Short-circuit Protection:	Yes / Cyclic
Voltage Drop I _e :	≤ 1.8 V
Vibration Resistance:	55 Hz (1mm)
Shock Resistance:	30 g (11 ms)
Degree of Protection:	IP67
Overtravel Speed:	UNT: 10 m/s; UNR: 3 m/s
Wire-break/	
Reverse Polarity Protection: Yes	

weldguard Protection: Yes, add "/S1589" to part number

Mounting Accessories

KLRC-UNT*

UNT-Adjusting Bracket




Part Number	Cylinder Diameter
KLRC-UNT1	.315-0.984 in [8-25 mm]
KLRC-UNT2	.984-2.480 in [25-63 mm]
KLRC-UNT3	2.480-5.118 in [63-130 mm]



KLZ*-INT

UNT-Stopper



Part Number	Tie Rod Diameter 'A'
KLZ1-INT	.295 in [7.5 mm]
KLZ2-INT	.374 in [9.5 mm]
KLZ3-INT	.433 in [11.0 mm]





KLDT-UNT*

UNT (INT) Cable Clip



Groove Width 'A'
.276 in [7.0 mm]
.370 in [9.4 mm]
.453 in [11.5 mm]
.496 in [12.6 mm]





ASB-*

KLR-2UNR



Part Number	Cylinder Diameter
ASB-1 STRAP	.276433 in [7-11 mm]
ASB-2 STRAP	.433748 in [11-19 mm]
ASB-3 STRAP	.709-1.142 in [18-29 mm]
ASB-4 STRAP	1.102-1.535 in [28-39 mm]
ASB-5 STRAP	1.496-1.929 in [38-49 mm]
ASB-6 STRAP	1.890-2.323 in [48-59 mm]
ASB-7 STRAP	2.283-2.717 in [58-69 mm]
ASB-8 STRAP	2.677-3.110 in [68-79 mm]
ASB-9 STRAP	3.071-3.504 in [78-89 mm]







TURCK Inc.

3000 Campus Drive Minneapolis, MN 55441 (763) 553-7300 Phone: (763) 553-0708 Fax: **Application Support:** 1-800-544-7769



MEXICO

TURCK MEXICO S. DE R.L. DE C.V. Carr. Saltillo-Zacatecas km 4.5 s/n Parque Industrial "La Angostura" Saltillo, COAH. C.P. 25070

Mexico

Phone: +52 (844) 411-6647/46 +52 (844) 482-6926 Fax: Local Toll Free: 01-800-01-88725 E-mail: ventasmexico@turck.com



CANADA

CHARTWELL AUTOMATION, INC. 140 Duffield Drive Markham, Ontario Canada, L6G 1B5

Phone: (905) 513-7100 (905) 513-7101 Toll Free: 1-877-513-7769



GERMANY WORLD HEADQUARTERS

Hans TURCK GmbH & Co. KG Witzlebenstrasse 7 D-45472 Muelheim an der Ruhr Federal Republic of Germany (+49) 208-49 52-0 Phone: (+49) 208-49 52 264



AUSTRALIA

TURCK Australia Pty. Ltd. Unit 5, 6-7 Gilda Court Mulgrave, Victoria 3170 Australia

Phone:

(+61) 3 9560 9066 Fax: (+61) 3 9560 1620 Local Toll Free: 1300 132566 E-mail: turckaustralia@turck.com

www.turck.com

©2010 by TURCK Inc. All rights reserved. No part of the publication may be reproduced without written permission.