

TURCK M8 picofast® Connectivity

4-Wire Cordsets, Threaded Coupling Nut

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 125 V, 2 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout	
<p>PKG ..M**</p>	<p>PKG 4M-* PKW 4M-*</p>	<p>PSG 4M-* PSW 4M-*</p>	<p>AWM PVC Yellow, 4x26 AWG, 105°C, 4.4 mm OD, Cable #RF50697-*M†, flexlife*</p>	<p>Female</p> <p>Male</p>	
<p>PKW ..M**</p>	<p>PKG 4M-*/S90 PKW 4M-*/S90</p>	<p>PSG 4M-*/S90 PSW 4M-*/S90</p>	<p>AWM TPU Black, 4x26 AWG, 90°C, 4.4 mm OD, Cable #RF50586-*M†, Cut/Abrasion Immune</p>		
<p>PKG 4M-*/S90/S101 PKW 4M-*/S90/S101</p>	<p>PKG 4M-*/S90/S101 PKW 4M-*/S90/S101</p>	<p>PSG 4M-*/S90/S101 PSW 4M-*/S90/S101</p>	<p>AWM TPU Black, 4x26 AWG, 90°C, 4.4 mm OD, Cable #RF50935-*M†, Cut/Abrasion Immune, flexlife-20, High Flex - Over 20 Million Cycles</p>		<p>1. BN 2. WH 3. BU 4. BK</p>
<p>PSG ..M**</p>	<p>PKG 4M-*/S90/S618 PKW 4M-*/S90/S618</p>	<p>PSG 4M-*/S90/S618 PSW 4M-*/S90/S618</p>	<p>AWM TPU Black, 4x26 AWG, 90°C, 4.4 mm OD, Cable #RF50602-*M†, Cut/Abrasion Immune, EMI/RFI Protection</p>		
<p>PSW ..M**</p>	<p>PKG 4M-*/S760 PKW 4M-*/S760</p>	<p>PSG 4M-*/S760 PSW 4M-*/S760</p>	<p>AWM PVC Black, 4x26 AWG, 105°C, 4.4 mm OD, Cable #RF50870-*M†, flexlife</p>		
<p>PKG 4M-*/S90/S653 PKW 4M-*/S90/S653</p>	<p>PKG 4M-*/S90/S653 PKW 4M-*/S90/S653</p>	<p>PSG 4M-*/S90/S653 PSW 4M-*/S90/S653</p>	<p>AWM TPU Black, 3x24 AWG, 90°C, 4.4 mm OD, Cable #RF50601-*M†, Cut/Abrasion Immune, EMI/RFI Protection</p>		<p>1. BN 2. Drain 3. BU 4. BK</p>

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is nickel plated brass.. "PKG..M"; "PKG..M" indicates stainless steel.

† See Section N for **reelfast** cable information.