

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Tool for processing ferrules according to DIN 46228-4, 0.5 mm² to 2.5 mm², equipped with pressure lock, magazine, cutting, stripping, twisting, and crimping unit.

Why buy this product

- ✓ Integrated pressure lock ensures consistently high-quality crimping
- ✓ Up to 30% time savings since the process steps required for assembling conductors can be carried out using only one tool
- ✓ Multifunctional crimping pliers for the processing of Taped ferrules according to DIN 46228-4
- ✓ Robust and durable due to use of resistant plastics and annealed metals
- ✓ Visualized process flows directly on the pliers simplify operation



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 STK |
| GTIN |  4 055626 042381 |
| GTIN | 4055626042381 |

Technical data

Dimensions

| | |
|------------------|---------|
| Length (b) | 180 mm |
| Width (a) | 31.5 mm |
| Height (c) | 100 mm |
| Stripping length | 8 mm |

General

| | |
|----------------------------------|--------------|
| Compression | Indent crimp |
| Type of contact | Ferrules |
| Min. AWG, flexible, multi-strand | 14 |

Multi-function tool - CRIMPFOX 4 IN 1 - 1200101

Technical data

General

| | |
|----------------------------------|---------------------|
| AWG max., flexible, multi-strand | 20 |
| Min. cross section | 0.5 mm ² |
| Max. cross section | 2.5 mm ² |
| AWG min | 20 |
| AWG max | 14 |
| Maximum stripping length | 11 mm |
| Weight | 240 g |
| Min. cross section | 0.5 mm ² |
| Max. cross section | 2.5 mm ² |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU x- DE.xx08.B.02974 |
|-----|---|--------------------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>