

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FK ..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FK 4.6-*	FS 4.6-*	6x22 AWG, 105°C, 250 V, 4 A Mates with 6-pin Cordsets	<p>Female</p> <p>Male</p>
<p>FK ..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FK 6-*	FS 6-*	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A Mates with 6-pin Cordsets	<p>Female</p> <p>Male</p>
<p>FK ..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FK 8-*	FS 8-*	8x24 AWG, 105°C, 60 VAC/75 VDC, 2 A Mates with 8-pin Cordsets	<p>Female</p>
	FK 8.6-*	FS 8.6-*	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A Mates with 8-pin Cordsets	<p>Male</p>

Receptacles

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FS."; "FSV." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.