

3-Wire Cordsets, Standard Duty

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>KB ..**</p>	KB 3T-* WKB 3T-*	SB 3T-* WSB 3T-*	AWM PVC Yellow, 3x22 AWG, 105°C, 5.1 mm OD, Cable #RF50531-*M†	
	KB 3T-*/S90 WKB 3T-*/S90	SB 3T-*/S90 WSB 3T-*/S90	AWM TPU Yellow, 3x18 AWG, 90°C, 5.7 mm OD, Cable #RF50547-*M†, Cut/Abrasion Immune	1. GN 2. RD/BK 3. RD/WH
<p>WKB ..**</p>	KB 3T-*/S105 WKB 3T-*/S105	SB 3T-*/S105 WSB 3T-*/S105	AWM PVC Yellow, 3x22 AWG, 105°C, 5.7 mm OD, Cable #RF50535-*M†, Braided Shield	
<p>SB ..**</p>	KB 3T-*/S749 WKB 3T-*/S749	SB 3T-*/S749 WSB 3T-*/S749	AWM PVC Yellow, 2x22 AWG, 105°C, 5.1 mm OD, Cable #RF50650-*M†, 3-pin with 2 conductors	1. N/C 2. BK 3. WH
	KB 3T-*/S1507 WKB 3T-*/S1507	SB 3T-*/S1507 WSB 3T-*/S1507	AWM TPE Grey, 3x20 AWG 105°C, 5.7 mm OD, Cable #RF50940-*M†, Flexlife-20, High Flex - Over 20 million cycles	
<p>WSB ..**</p>	KB 3T-*/XOR WKB 3T-*/XOR	SB 3T-*/XOR WSB 3T-*/XOR	AWM PVC Yellow, 3x18 AWG, 80°C, 250°C short term, 5.7 mm OD, Cable #RF04159-*M†, Weld Flash Immune, High Temp Immune	1. GN 2. RD 3. RD/WH

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "KB .."; "KBK .." indicates nylon and "KBV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.