

# TURCK Splitters

## multibox® 2 - Branch Molded Splitters

- Consolidate 2 Sensors/Actuators into One
- M8 *picofast*® or M12 *eurofast*® Connector Branches
- Tough TPU Construction
- IEC IP67 Protection
- NEMA 1, 3, 4



Drawing	Part Number	Features	Wiring Diagram
	<b>YB2-FSM 4.5-2FKM 4.5</b> (Fits 8MB12 j-boxes)	2 <i>eurofast</i> branches, black TPU, 80°C, 30 VAC/36 VDC, 4 A, combine 2 sensors/actuators with <i>eurofast</i> connector branches into one	
	<b>YB2-FSM 4.5-2FKM 4.5/S1063</b> (Fits VB J-boxes)	2 <i>eurofast</i> branches, grey TPU, 80°C, 30 VAC/36 VDC, 4 A, combine 2 sensors/actuators with <i>eurofast</i> connector branches into one	
	<b>YB2-FSM 4.4/2PKG 3M</b>	2 <i>picofast</i> branches, black TPU, 80°C, 30 VAC/36 VDC, 2 A, combine 2 sensors/actuators with <i>picofast</i> connector branches into one	
	<b>YBZ2-FSM 4.5/2FKM 4.5/S771</b>	2 <i>eurofast</i> branches, black TPU, 80°C, 30 VAC/36 VDC, 4 A, combine 2 sensors/actuators with <i>eurofast</i> connector branches into one	
	<b>YBZ2-PX3-FSM 4.5/2FKM 4.5</b>	2 <i>eurofast</i> branches, transparent TPU, 80°C, 36 VDC, 4 A, combine 2 sensors/actuators with <i>eurofast</i> connector branches into one, LEDs	

Standard coupling nut material is nickel plated brass.

