

## 2, 3 and 4-Wire Receptacles, Front Mount, 1/2-14 NPSM Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>FKB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 2-*/14.5	FSB 2-*/14.5	2x18 AWG, 105°C	<p><b>Female</b></p> <p><b>Male</b></p> <p>1. BN 2. BU</p>
<p><b>FSB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 3-*/14.5	FSB 3-*/14.5	3x22 AWG, 105°C	<p><b>Female</b></p> <p><b>Male</b></p> <p>1. GN 2. RD/BK 3. RD/WH</p>
	FKB 3-*/14.5/S690	FSB 3-*/14.5/S690	3x18 AWG, 105°C	<p><b>Male</b></p>
<p><b>FSB ...</b></p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 4-*/14.5	FSB 4-*/14.5	4x22 AWG, 105°C	<p><b>Female</b></p> <p><b>Male</b></p> <p>1. RD/BK 2. RD/WH 3. RD 4. GN</p>
	FKB 4-*/14.5	FSB 4-*/14.5	4x22 AWG, 105°C	<p><b>Male</b></p>

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.  
Standard housing material is nickel plated brass."FSB ..".  
To specify PVC jacketed cable, add "/S717" to the end of the part number.