

## CL3R/CMR Non-shielded 16 AWG & 18 AWG 300V

CL3R - Nonshielded Conductors  
PVC Insulation & Jacket  
300 Volt  
18 AWG & 16 AWG



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Stranded bare copper to ASTM B-3, B-8, and B-286

### Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC) Includes ripcord

### Standards:

- NEC Article 725 Type CL3R
- CSA CMG FT-4

### Category Insulation Description:

- Color coded Polyvinyl Chloride (PVC)

### Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>	<b>Material Weight (KG/KM)</b>
DS91802	18	2	0.009	0.015	0.154	17.1	25
DS91803	18	3	0.009	0.015	0.166	23.6	35
DS91804	18	4	0.009	0.015	0.187	28.9	43
DS91806	18	6	0.009	0.015	0.225	42	62
DS91808	18	8	0.009	0.015	0.245	56.4	83
DS91810	18	10	0.009	0.015	0.27	69	102
DS91812	18	12	0.009	0.015	0.29	84	125
DS91602	16	2	0.01	0.015	0.178	25	37
DS91603	16	3	0.01	0.015	0.196	39	58
DS91604	16	4	0.01	0.015	0.209	45.1	67

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**