

Electronic overload relays

EF205, EF370



EF205-210

63 to 380 A

Setting range	Short-circuit protective device	Trip class	Type	Order code	Weight (1 pce)
A					kg
Suitable for AF145, AF185, AF190, AF205					
63 ... 210	1250 A, fuse type gG	10E, 20E, 30E	EF205-210 ¹	1SAX531001R1101	1.210
Suitable for AF210, AF260, AF265, AF300, AF305, AF370					
115 ... 380	1600 A, fuse type gG	10E, 20E, 30E	EF370-380 ¹	1SAX611001R1101	1.430

¹ ATEX is valid for products produced from week 42, 2015. IECEx is valid for products produced from week 15, 2017.

Accessories

Description	Suitable for	Type	Order code	Weight (1 pce)
Reset push button	E16, EF, TF, T16, TA200	KPR-101L	1SFA616162R1014	0.027
Terminal shroud	EF205	LT200E	1SAX501904R0001	0.085
Terminal shroud	EF370	LT320E	1SAX601904R0001	0.105
Remote reset coil 24-30 V DC		DRS-F-01	1SAX101911R1001	0.077
Remote reset coil 48-60 V DC		DRS-F-02	1SAX101911R1002	0.077
Remote reset coil 110-127 V DC	EF19, EF45, EF65,	DRS-F-03	1SAX101911R1003	0.077
Remote reset coil 220-240 V DC	EF96, EF146,	DRS-F-04	1SAX101911R1004	0.077
Remote stop coil 24-30 V AC/DC	EF205, EF370,	DRS-F-EF-01	1SAX101911R1011	0.077
Remote stop coil 48-60 V AC/DC	EF460, EF750	DRS-F-EF-02	1SAX101911R1012	0.077
Remote stop coil 110-127 V AC/DC		DRS-F-EF-03	1SAX101911R1013	0.077
Remote stop coil 220-240 V AC/DC		DRS-F-EF-04	1SAX101911R1014	0.077



EF370-380



KPR-101L



DRS-F