

3-pole contactors

AF190 ... AF370



AF205-30-00



AF370-30-00

90 to 200 kW - AC / DC operated

IEC		UL / CSA		Rated control circuit voltage		Auxiliary contacts fitted		Type ¹	Order code	Weight Pkg (1 pce)
Rated operational power 400 V AC-3 kW	current $\theta \leq 40^\circ\text{C}$ AC-1 A	3-phase motor rating 480 V hp	General use rating 600 V AC A	Uc min. ... Uc max.		I L Y				
				V 50/60 Hz	V DC					
90	275	125	250	24...60	20...60	0	0	AF190-30-00-11	1SFL487002R1100	3.000
				48...130	48...130	0	0	AF190-30-00-12	1SFL487002R1200	3.000
				100...250	100...250	0	0	AF190-30-00-13	1SFL487002R1300	3.000
				250...500	250...500	0	0	AF190-30-00-14	1SFL487002R1400	3.000
110	350	150	300	24...60	20...60	0	0	AF205-30-00-11	1SFL527002R1100	3.000
				48...130	48...130	0	0	AF205-30-00-12	1SFL527002R1200	3.000
				100...250	100...250	0	0	AF205-30-00-13	1SFL527002R1300	3.000
				250...500	250...500	0	0	AF205-30-00-14	1SFL527002R1400	3.000
132	400	200	350	24...60	20...60	0	0	AF265-30-00-11	1SFL547002R1100	4.605
				48...130	48...130	0	0	AF265-30-00-12	1SFL547002R1200	4.605
				100...250	100...250	0	0	AF265-30-00-13	1SFL547002R1300	4.605
				250...500	250...500	0	0	AF265-30-00-14	1SFL547002R1400	4.605
160	500	250	400	24...60	20...60	0	0	AF305-30-00-11	1SFL587002R1100	4.605
				48...130	48...130	0	0	AF305-30-00-12	1SFL587002R1200	4.605
				100...250	100...250	0	0	AF305-30-00-13	1SFL587002R1300	4.605
				250...500	250...500	0	0	AF305-30-00-14	1SFL587002R1400	4.605
200	600	300	520	24...60	20...60	0	0	AF370-30-00-11	1SFL607002R1100	4.605
				48...130	48...130	0	0	AF370-30-00-12	1SFL607002R1200	4.605
				100...250	100...250	0	0	AF370-30-00-13	1SFL607002R1300	4.605
				250...500	250...500	0	0	AF370-30-00-14	1SFL607002R1400	4.605

¹For other auxiliary contacts arrangements, please contact your ABB local sales organization.



AF205-30-00



AF370-30-00

90 to 200 kW - AC / DC operated for faster utilization - with built-in PLC interface

IEC		UL / CSA		Rated control circuit voltage		Auxiliary contacts fitted		Type ¹	Order code	Weight Pkg (1 pce)
Rated operational power 400 V AC-3 kW	current $\theta \leq 40^\circ\text{C}$ AC-1 A	3-phase motor rating 480 V hp	General use rating 600 V AC A	Uc min. ... Uc max.		I L Y				
				V 50/60 Hz	V DC					
90	275	125	250	100...250	100...250	0	0	AF190-30-00-33	1SFL487002R3300	3.000
				250...500	250...500	0	0	AF190-30-00-34	1SFL487002R3400	3.000
110	350	150	300	100...250	100...250	0	0	AF205-30-00-33	1SFL527002R3300	3.000
				250...500	250...500	0	0	AF205-30-00-34	1SFL527002R3400	3.000
132	400	200	350	100...250	100...250	0	0	AF265-30-00-33	1SFL547002R3300	4.605
				250...500	250...500	0	0	AF265-30-00-34	1SFL547002R3400	4.605
160	500	250	400	100...250	100...250	0	0	AF305-30-00-33	1SFL587002R3300	4.605
				250...500	250...500	0	0	AF305-30-00-34	1SFL587002R3400	4.605
200	600	300	520	100...250	100...250	0	0	AF370-30-00-33	1SFL607002R3300	4.605
				250...500	250...500	0	0	AF370-30-00-34	1SFL607002R3400	4.605

¹For other auxiliary contacts arrangements, please contact your ABB local sales organization.