

18 AWG – 16×30 Stranded Tinned Copper – 1 pair

Multiconductor - 300 Volt
Overall Aluminum Shield
Polyethylene Insulation



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded tinned copper

Shield:

- 100% aluminum foil/polyester with stranded tinned copper drain wire

Temperature:

- -20C to 75C

Standards:

- CEC CM
- NEC type CM
- 300 Volt rated 60°C rated

Category Insulation Description:

- Polyethylene (PE), twisted pair

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Due to the improved noise immunity of twisted pairs, they generally permit higher data speeds than multi-conductor cables

Part Number Table

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D11802	18	1	16x30 TC	0.019	0.028	0.202	21
D11802-BS	18	1	16x30 TC	0.019	0.028	0.23	36

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. *D11802-BS: The jacket and the shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of the foil shield. Also available in a pull box.

Selling Exclusively Through Distribution Since 1977 [™] | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC