

## 18 AWG – 19×30 Stranded Tinned Copper – 4 conductor

Multi-Conductor - 300 Volt  
Overall Aluminum Shield  
S-R PVC Insulation - 75°C



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Tinned copper

### Shield Drain:

---

- Aluminum-polyester shield Tinned copper drain wire with 100% shield coverage

### Applications:

---

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise

### Category Insulation Description:

---

- Semi-Rigid Polyvinyl Chloride (SR-PVC), conductors cabled

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

### Standards:

---

- UL Rated - 75°C
- Voltage: UL 300 Volt

Part Number Table

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D21804	18	4	19x30 TC	0.01	0.035	0.227	39

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC