


Product description	M8 Female cable connector, Contacts: 3, shielded, moulded on the cable, IP67/IP69K, UL 2238, M8x1.0, PUR, black, 3 x 0.34 mm², 5 m
Area	M8
Coding	A-coded
Series	718
Part no.	77 3506 0000 50703-0500


Illustration (may vary)



Scale drawing



Contact arrangement (Plug-in side)



- 1

brown
- 3

blue
- 4

black
- Shielded versions:
shield on housing

Cable length tolerance

<i>cable length</i>	<i>tolerance</i>
≥ 0,10 m	+ 0,03 m
≥ 0,20 m	+ 0,04 m
≥ 0,50 m	+ 0,07 m
≥ 1,00 m	+ 0,10 m
≥ 2,00 m	+ 0,15 m
≥ 5,00 m	+ 0,20 m
≥ 10,0 m	+ 0,25 m
≥ 20,0 m	+ 0,35 m

Technical data

General features

Part no.	77 3506 0000 50703-0500
Connector design	Female cable connector
Coding	A-coded
Cable length	5 m (Standard 2 m and 5 m. Other lengths are available on request.)
Version	Connector socket straight
Connector locking system	screw

Product description	M8 Female cable connector, Contacts: 3, shielded, moulded on the cable, IP67/IP69K, UL 2238, M8x1.0, PUR, black, 3 x 0.34 mm², 5 m
Area	M8
Coding	A-coded
Series	718
Part no.	77 3506 0000 50703-0500

Termination	moulded on the cable
Degree of protection	IP67/IP69K
Connection cross-section	0.34 mm ² / AWG 22
Temperature range from/to	-25 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	75.00
Customs tariff number	85444290
Country of Origin	DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	1500 V
Rated current	4.0 A
Insulation resistance	> 10 ⁸ Ω
Pollution degree	3
Overvoltage category	III
Insulating material group	II
EMC compliance	shielded
Shield connection	Screen on shield sleeve

Material

Contact body material	PUR
Contact material	CuZn (brass)
Contact plating	Au (gold)
Locking material	CuZn (brass)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	15d48688-8c0b-4673-8d55-ca321975205d

Cable data - Structure of the cable

Cable diameter	4.6 mm
Cross section	3 x 0.34 mm ²
Sheath material	PUR
Single-lead insulation	PP9Y halogen-free
Single-lead structure	42 x 0.10 mm
Cable color	black

Cable data - Electrical properties

Conductor resistance	60 Ω/Km (20°C)
----------------------	----------------

Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø
Bending cycles	> 2 million

Product description	M8 Female cable connector, Contacts: 3, shielded, moulded on the cable, IP67/IP69K, UL 2238, M8x1.0, PUR, black, 3 x 0.34 mm², 5 m
Area	M8
Coding	A-coded
Series	718
Part no.	77 3506 0000 50703-0500

Permitted acceleration	5 m/s² + 1 m/s²
Travel distance, horizontal	5 m/s² -> 5 m
Travel distance, vertical	5 m/s² -> 2 m
Travel speed	≤ 200 m/min (5 m horizontal distance)

Cable data - Thermal properties

Temperature range cable in move from/to	-25 °C / 90 °C
Temperature range cable fixed from/to	-50 °C / 90 °C

Cable data - Other features

Halogen free	yes
--------------	-----

Authorization/approvals

Approvals	UL 2238
-----------	---------

Declarations of conformity

RoHS Directive	EN IEC 63000:2018
----------------	-------------------

Product description	M8 Female cable connector, Contacts: 3, shielded, moulded on the cable, IP67/IP69K, UL 2238, M8x1.0, PUR, black, 3 x 0.34 mm², 5 m
Area	M8
Coding	A-coded
Series	718
Part no.	77 3506 0000 50703-0500

General Disclaim Notice

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 40 cNm).