# VAL-MS 230 IT ST - Type 2 surge protection plug

2807599

https://www.phoenixcontact.com/us/products/2807599

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Surge protection connector type 2 with high-capacity varistor for VAL-MS base element, thermal monitoring, visual fault warning. Design: 230 V AC (IT system)

## Your advantages

- Quality proven millions of times over in the widest range of applications
- Rapid installation with bridges, thanks to industry-standard overall width of 1 HP
- Easy testing and insulation measurement, thanks to pluggable protection modules
- Wide range of applications due to various nominal voltages
- High degree of modularity provides individual solutions for every application

## Commercial data

| | |
|---|---|
| Item number | 2807599 |
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL18 |
| Product key | CL1321 |
| GTIN | 4017918075286 |
| Weight per piece (including packing) | 50.8 g |
| Weight per piece (excluding packing) | 47.55 g |
| Customs tariff number | 85363030 |
| Country of origin | DE |

## Technical data

### Notes

| | |
|---|---|
| Order information: | Use in DC applications on request |

General

| | |
|---|---|
| Note | Usable in all low-voltage systems between L-N or L-PEN.<br>Only usable in IT Systems between L-PE, if the exposed-conductive-parts (bodies) of the equipment of the low-voltage installation is connected to the earthing arrangement of the transformer substation. (interconnected earthing arrangement of the HV-transformer substation with the bodies of the LV-installation. $R_E = R_A$ accordance to IEC 60364-4-442 / VDE 0100-442 Fig. 44D / Example a) |

### Product properties

| | |
|---|---|
| Product type | Replacement plug |
| Product family | VALVETRAB MS |
| IEC test classification | II |
| | T2 |
| EN type | T2 |
| IEC power supply system | TN |
| | TT |
| | IT |
| Type | Male |
| Number of positions | 1 |
| Surge protection fault message | optical |
| Arrester can be tested with CHECKMASTER from software version: | From SW rev. 1.10 |
| Number of ports | One |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Pollution degree | 2 |


### Electrical properties

| | |
|---|---|
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |

### Connection data

| | |
|---|---|
| Connection method | pluggable |

### Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Width | 17.5 mm |
| Height | 52.4 mm |
| Depth | 55.3 mm |
| Horizontal pitch | 1 HP |

## Material specifications

| | |
|---|---|
| Color | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA 6.6 |
| Material group | I |
| Housing material | PA 6.6 |

## Protective circuit

| | |
|---|---|
| Mode of protection | L-N |
| | L-PE |
| | L-PEN |
| Direction of action | 1L-N/PE |
| Nominal voltage $U_N$ | 240/415 V AC (TN) |
| | 240/415 V AC (TT) |
| | 230 V AC (IT) |
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |
| Maximum continuous operating voltage $U_C$ | 385 V AC |
| Protective conductor current $I_{PE}$ | ≤ 0.45 mA |
| Standby power consumption $P_C$ | ≤ 175 mVA |
| Nominal discharge current $I_n$ (8/20) µs | 20 kA |
| Maximum discharge current $I_{max}$ (8/20) µs | 40 kA |
| Short-circuit current rating $I_{SCCR}$ | 25 kA |
| Voltage protection level $U_p$ | ≤ 1.8 kV |
| Residual voltage $U_{res}$ | ≤ 1.8 kV (at $I_n$) |
| | ≤ 1.6 kV (at 10 kA) |
| | ≤ 1.4 kV (at 5 kA) |
| | ≤ 1.3 kV (at 3 kA) |
| TOV behavior at $U_T$ | 415 V AC (5 s / withstand mode) |
| | 440 V AC (120 min / withstand mode) |
| Response time $t_A$ | ≤ 25 ns |
| Max. backup fuse with branch wiring | 125 A (gG) |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |
| Shock (operation) | 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z) |
| Vibration (operation) | 5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

## Approvals

UL specifications

| | |
|---|---|
| Maximum continuous operating voltage MCOV (L-N) | 385 V AC |
| Nominal discharge current $I_n$ (L-N) | 20 kA |
| Mode of protection | L-N |
| Nominal voltage | 230 V AC |
| Power distribution system | Single phase |
| Nominal frequency | 50/60 Hz |
| Measured limiting voltage MLV (L-N) | 2200 V |
| SPD Type | 4CA |

## Standards and regulations


| | |
|---|---|
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

## Mounting

| | |
|---|---|
| Mounting type | on base element |

## Drawings

Dimensional drawing




Circuit diagram



## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27171292 |
| ECLASS-15.0 | 27171292 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC002496 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 0.622 kg CO2e |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com