THERMOMARK GO ACCU - Battery

0805009

https://www.phoenixcontact.com/us/products/0805009

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Battery for mobile operation of the THERMOMARK GO and THERMOMARK GO.K / THERMOFOX printers.

ELEKTROGERÄTE RÜCKNAHME

Commercial data

Item number	0805009
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG03
Product key	BG122Z
GTIN	4055626269139
Weight per piece (including packing)	117 g
Weight per piece (excluding packing)	116 g
Customs tariff number	85076000
Country of origin	CN

Technical data

Product properties

Product type	Battery module
Battery-operated voltage	7.40 V

Electrical properties

Battery

Battery capacity	2.60 Ah

Energy storage

Battery capacity	2.6 Ah
Battery technology	Lithium-Ion

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	5 °C ... 40 °C
Ambient temperature (storage/transport)	23 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Shelf life	1 Year

Classifications

ECLASS

ECLASS-13.0	21052902
ECLASS-15.0	21052902

ETIM

ETIM 10.0	EC001199

UNSPSC

UNSPSC 21.0	26111700

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com