# VAL-MS-T1/T2 335/12.5/4+0 - Lightning/surge arrester type 1/2

2800645

https://www.phoenixcontact.com/us/products/2800645

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Universal varistor-based plug-in lightning/surge arrester for 3-phase power supply networks with separate N and PE (5-conductor system: L1, L2, L3, N, PE).

## Your advantages

- Quality proven millions of times over in the widest range of applications
- Rapid installation with bridges, thanks to industry-standard overall width of 1 HP
- Easy testing and insulation measurement, thanks to pluggable protection modules
- Can be used in lightning protection level III and IV due to discharge capacity of 12.5 kA per position
- Vibration-resistant latching ensures the plug remains firmly in place

## Commercial data

| | |
|---|---|
| Item number | 2800645 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL18 |
| Product key | CL1151 |
| GTIN | 4046356624770 |
| Weight per piece (including packing) | 706.1 g |
| Weight per piece (excluding packing) | 712.22 g |
| Customs tariff number | 85363030 |
| Country of origin | DE |

## Technical data

### Product properties

| | |
|---|---|
| Product type | Arrester combination |
| Product family | VALVETRAB MS |
| IEC test classification | I / II |
| | T1 / T2 |
| EN type | T1 / T2 |
| IEC power supply system | TN-S |
| Type | DIN rail module, two-section, divisible |
| Number of positions | 4 |
| Surge protection fault message | optical |
| Number of ports | One |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Pollution degree | 2 |


### Electrical properties

| | |
|---|---|
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |

### Connection data

| | |
|---|---|
| Connection method | Screw connection |
| Screw thread | M5 |
| Tightening torque | 3 Nm (1.5 mm² ... 16 mm²) |
| | 4.5 Nm (25 mm² ... 35 mm²) |
| Stripping length | 16 mm |
| Conductor cross-section flexible | 1.5 mm² ... 25 mm² |
| Conductor cross-section rigid | 1.5 mm² ... 35 mm² |
| Conductor cross-section AWG | 15 ... 2 |
| Connection method | Fork-type cable lug |
| Conductor cross-section flexible | 1.5 mm² ... 16 mm² |

### Dimensions

| | |
|---|---|
| Dimensional drawing |   |
| Width | 71.2 mm |
| Height | 89.8 mm |
| Depth | 77.5 mm (incl. DIN rail 7.5 mm) |
| Horizontal pitch | 4 HP |

## Material specifications

| | |
|---|---|
| Color | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA 6.6/PBT |
| Material group | I |
| Housing material | PA 6.6 |
| | PBT |

## Mechanical properties

Mechanical data

| | |
|---|---|
| Open side panel | No |

## Protective circuit

| | |
|---|---|
| Mode of protection | L-PE |
| | N-PE |
| Direction of action | 3L-N/PE |
| Nominal voltage $U_N$ | 240/415 V AC (TN-S) |
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |
| Maximum continuous operating voltage $U_C$ | 335 V AC |
| Rated load current $I_L$ | 80 A |
| Protective conductor current $I_{PE}$ | ≤ 3.2 mA |
| Standby power consumption $P_C$ | ≤ 1080 mVA |
| Nominal discharge current $I_n$ (8/20) µs | 12.5 kA |
| Maximum discharge current $I_{max}$ (8/20) µs | 50 kA |
| Impulse discharge current (10/350) µs, charge | 6.5 As |
| Impulse discharge current (10/350) µs, specific energy | 39 kJ/Ω |
| Impulse discharge current (10/350) µs, peak value $I_{imp}$ | 12.5 kA |
| Total discharge current $I_{Total}$ (8/20) µs | 200 kA |
| Total discharge current $I_{Total}$ (10/350) µs | 50 kA |
| Short-circuit current rating $I_{SCCR}$ | 25 kA |
| Voltage protection level $U_p$ | ≤ 1.2 kV |
| | ≤ 1.6 kV (30 kA - 8/20 µs) |
| Residual voltage $U_{res}$ | ≤ 1.2 kV (at $I_n$) |
| | ≤ 1.1 kV (at 10 kA) |
| | ≤ 1 kV (at 5 kA) |
| | ≤ 0.9 kV (at 3 kA) |
| TOV behavior at $U_T$ | 415 V AC (5 s / withstand mode) |
| | 457 V AC (120 min / safe failure mode) |
| Response time $t_A$ | ≤ 25 ns |
| Max. backup fuse with V-type through wiring | 80 A (gG - 16 mm²) |

| | |
|---|---|
| Max. backup fuse with branch wiring | 160 A (gG) |

Additional technical data

| | |
|---|---|
| Maximum discharge current $I_{max}$ (8/20) µs | 65 kA |

## Environmental and real-life conditions

Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 (only when all terminal points are used) |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |
| Shock (operation) | 30g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z) |
| Vibration (operation) | 7.5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

## Approvals

UL specifications

| | |
|---|---|
| Maximum continuous operating voltage MCOV (L-L) | 670 V AC |
| Maximum continuous operating voltage MCOV (L-N) | 670 V AC |
| Maximum continuous operating voltage MCOV (L-G) | 335 V AC |
| Maximum continuous operating voltage MCOV (N-G) | 335 V AC |
| Nominal discharge current $I_n$ (L-L) | 20 kA |
| Nominal discharge current $I_n$ (L-N) | 20 kA |
| Nominal discharge current $I_n$ (L-G) | 20 kA |
| Nominal discharge current $I_n$ (N-G) | 20 kA |
| Mode of protection | L-L |
| | L-N |
| | L-G |
| | N-G |
| Nominal voltage | 415/240 V AC |
| Power distribution system | Wye |
| Nominal frequency | 50/60 Hz |
| Measured limiting voltage MLV (L-L) | 3650 V |
| Measured limiting voltage MLV (L-N) | 3650 V |
| Measured limiting voltage MLV (L-G) | 2630 V |
| Measured limiting voltage MLV (N-G) | 2630 V |
| SPD Type | 4CA |

UL connection data

| | |
|---|---|
| Tightening torque | 30 $lb_f$-in. |
| Conductor cross-section AWG | 14 ... 2 |

## Standards and regulations


| | |
|---|---|
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail: 35 mm |

## Drawings

Dimensional drawing




# VAL-MS-T1/T2 335/12.5/4+0 - Lightning/surge arrester type 1/2


2800645

https://www.phoenixcontact.com/us/products/2800645

Product drawing



Circuit diagram



## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 27171201 |
| ECLASS-15.0 | 27171201 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC000381 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 5.98 kg CO2e |


Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com