MSTBC-MT 1,5-2,5 - Crimp contact

3190551

https://www.phoenixcontact.com/us/products/3190551

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Module female contact, is inserted into the plug housing MSTBC after crimping the conductor, for conductors from 1.5 to 2.5 mm^2

Commercial data

Item number	3190551
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	AA03
Product key	AACCEG
GTIN	4017918093389
Weight per piece (including packing)	0.48 g
Weight per piece (excluding packing)	0.46 g
Customs tariff number	85366990
Country of origin	CN

Technical data

Product properties

Product type	Crimp contact
Product family	MSTBC-MT
Pitch	0 mm

Connection data

Connection method	Crimp connection
Contact connection type	Socket
Stripping length	4 mm ... 4.1 mm
Conductor cross-section flexible	1.5 mm² ... 2.5 mm²
Conductor cross-section AWG	16 ... 14
Wire diameter including insulation	2.11 mm ... 3.1 mm

Material specifications

Contact surface	Tin Sn
Contact surface material	Tin
Metal surface contact area (top layer)	Tin Sn)

Dimensions

Pitch	-

Electrical properties

Nominal current I_N	12 A

Packaging specifications

Type of packaging	Bulk goods

Classifications

ECLASS

ECLASS-13.0	27460403
ECLASS-15.0	27460403

ETIM

ETIM 10.0	EC000796

UNSPSC

UNSPSC 21.0	39121500

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com