CAPAROC PM EIP - Feed-in module

1393553

https://www.phoenixcontact.com/us/products/1393553

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CRA READY



Power module with EtherNet/IP™ interface for supplying the CAPAROC circuit breaker system with 12 V DC or 24 V DC. Additional system interface for communication with the power supply. For DIN rail installation via the CAPAROC current rails.

Product description

Further information about the CAPAROC product family can be found in the online manual at: phoenixcontact.com/caparoc-help

Your advantages

- The benchmark that you can customize by selecting single signals and resets all the way to EtherNet/IP™ communication
- Particularly easy operation for everyone with tool-free assembly, direct feed-in to the busbar, and clear operating states
- Exceptionally easy design-in thanks to the comprehensive digital data packet and EtherNet/IP™ function blocks for Studio 5000

ELEKTROGERÄTE RÜCKNAHME

Commercial data

Item number	1393553
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL11
Customs tariff number	85363030

Country of origin	DE

Technical data

Notes

Note on application	As things stand now, we are preparing the product so that, as of December 11, 2027, it will comply with the requirements of the EU Cyber Resilience Act (CRA) based on the information currently available regarding the CRA.

General

Note	LABS release – in accordance with test specification VW PV 3. 10.7:2005-0
	When connecting the conductor, make sure that the CAPAROC modules are not pulled apart due to tensile force. Gaps must not be created between the modules.

Product properties

Product type	Device circuit breakers
Product family	CAPAROC
Type	Plug-in module
Number of slots	4

Insulation characteristics

Protection class	III
Pollution degree	2

System properties

EtherNet/IP™

Device function	EtherNet/IP™ adapter
Addressing	DHCP (default), BootP, static, ACD
Topology	Line
	Star
	Ring

Electrical properties

General

Operating voltage	10 V DC ... 30 V DC
Rated voltage	12 V DC
	24 V DC
Rated current I_N	45 A (Total current input)
Rated surge voltage	0.5 kV
Tripping method	E (electronic)
Feedback resistance	max. 35 V DC
Dielectric strength	35 V DC (Load circuit)
Efficiency	> 99 %
Closed circuit current I_0	typ. 46 mA (no load at 24 V)

Power dissipation	typ. 1.1 W (no load at 24 V)
	< 4.5 W (at 40 A)
Temperature derating	45 A (Total current at 60°C)
	20 A (Total current at 65 °C)
	45 A (Total current at 60°C, in accordance with UL)
MTBF (IEC 61709, SN 29500)	7242508.37 h (at 25 °C with 21 % load)
	3958056.77 h (at 40°C with 34.25% load)
	764697.81 h (at 60°C with 100% load)
Voltage drop	0.082 V (at 40 A)

Load circuit

Undervoltage switch-off	≤ 9.2 V DC (active)
	≥ 10.2 V DC (inactive)
Overvoltage switch-off	≥ 30.5 V DC (active)
	≤ 29.5 V DC (inactive)

Connection data

Main circuit IN+

Connection method	Push-in connection
Stripping length	18 mm
Conductor cross-section AWG	20 ... 8
Conductor cross-section, flexible, with ferrule, with plastic sleeve	0.5 mm² ... 16 mm²
Conductor cross-section, flexible, with ferrule, without plastic sleeve	0.5 mm² ... 16 mm²

Main circuit IN-

Connection method	Push-in connection
Stripping length	18 mm
Conductor cross-section AWG	20 ... 8
Conductor cross-section, flexible, with ferrule, with plastic sleeve	0.5 mm² ... 16 mm²
Conductor cross-section, flexible, with ferrule, without plastic sleeve	0.5 mm² ... 16 mm²

System communication

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross-section rigid	0.2 mm² ... 1.5 mm²
Conductor cross-section AWG	24 ... 16
Conductor cross-section, flexible, with ferrule, with plastic sleeve	0.2 mm² ... 0.75 mm²
Conductor cross-section, flexible, with ferrule, without plastic sleeve	0.2 mm² ... 1.5 mm²

Interfaces

EtherNet/IP™


Maximum system extension	≤ 16 (CAPAROC modules alignable)

Interface type	Ethernet
Number	2
Transmission speed	10 Mbps 100 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Protocols supported	EtherNet/IP™

Signaling

Connection X1 LED green	lit (connect)
Connection X1 LED yellow	lit (traffic)
Connection X2 LED green	lit (connect)
Connection X2 LED yellow	lit (traffic)
Power (PWR) LED green	lit (Supply voltage within the operating voltage range)
	3x flashing (Global programming lock deactivated)
Power (PWR) LED red	lit (Supply voltage outside the operating voltage range)
	5x flashing (Factory reset command accepted)
Power (PWR) LED yellow	lit (PWR button pressed)
	3x flashing (Global programming lock activated)
NET LED off	off (No voltage present at the device or no IP address configured)
NET LED green	lit (Communication with the controller present)
	flashing (IP address available, no communication with the controller)
NET LED red	lit (Address Conflict Detection (ACD): “Duplicate IP.” Device has detected that its IP address is already in use in the network.)
NET LED red-green	flashing (Device initialization self-test)
MOD LED off	off (No supply voltage)
MOD LED green	lit (Normal operation)
	flashing (The device is not yet configured)
MOD LED red-green	flashing (Device initialization self-test)
MOD LED red	lit (Error (EtherNet/IP™: “Major unrecoverable fault”), e.g., program crash in the controller)
	flashing (Error (EtherNet/IP™: “Major recoverable fault”), e.g., inconsistent or incorrect parameterization)
Ready (RDY) LED yellow-green	flashing (Firmware installation running)
Ready (RDY) LED yellow	lit (Firmware installation failed, perform manual voltage reset)
Ready (RDY) LED green	lit (Firmware started successfully)

Dimensions

Dimensional drawing	
Width	24.8 mm

Height	132.4 mm
Depth	111.3 mm (incl. DIN rail 7.5 mm)

Material specifications

Color	light gray (RAL 7035)
Material	PA 6
	PA 6
	PA 6
	PC
Flammability rating according to UL 94	V-0

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-30 °C ... 65 °C
	-30 °C ... 60 °C (in acc. with UL)
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	≤ 4000 m (amsl)
Humidity test	96 h, 95 % RH, 40 °C
Shock (operation)	30g (11 ms period, half-sine shock pulse, according to IEC 60068-2-27)
	25g (6 ms duration, half-sine shock pulse in accordance with IEC 60068-2-27, continuous shock)
Vibration (operation)	5g (10 Hz ... 150 Hz / 10 cycles / axis / X, Y, Z)

Standards and regulations


Standards/specifications	EN 61000-6-2
Note	EMC – Immunity for industrial areas
Standards/specifications	EN 61000-6-4
Note	EMC – Immunity for industrial areas
Standards/specifications	EN 61000-6-8
Note	EMC interference emission for professional devices that are used in business and commercial areas as well as in small businesses
Standards/specifications	EN 60068-2-78
Note	Environmental influences – Moisture and heat, constant
Standards/specifications	EN 50178
Note	Equipping power installations with electronic equipment
Standards/specifications	EN 60068-2-6
Note	Environmental influences – Vibrations (sinusoidal)
Standards/specifications	EN 60068-2-27
Note	Environmental influences – Shocks

Mounting


Mounting type	pluggable onto CAPAROC CR… current rail

Drawings


Dimensional drawing



Product drawing




Schematic diagram




When using the power module with an EtherNet/IP™ interface (CAPAROC PM EIP), max. 16 circuit breaker modules can be set. Any number of extra potential distribution modules can be added.

Diagram



Block diagram



Classifications

ECLASS

ECLASS-13.0	27140401
ECLASS-15.0	27140401

ETIM

ETIM 10.0	EC003538

UNSPSC

UNSPSC 21.0	39121400

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com