# FL SWITCH 1105N-2SFP - Industrial Ethernet Switch

1085171

https://www.phoenixcontact.com/us/products/1085171

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CRA READY



Narrow Ethernet switch, five RJ45 ports with 10/100/1000 Mbps on all ports, automatic data transmission speed detection, autocrossing function, and QoS

## Your advantages

- Jumbo frame support (frame size up to 9216 bytes/frame)
- RJ45 ports support a transmission speed of 10/100/1000 Mbps
- QoS-prioritized (Quality of Service) messages
- Local diagnostic indicators with LEDs
- Enhanced traffic prioritization for automation protocols
- PROFINET PTCP filter for reliable communication on PROFINET networks
- Energy-efficient Ethernet in accord. with IEEE 802.3az
- PROFINET conformance Class A for real-time data exchange, alarms, and diagnostics
- Auto negotiation and autocrossing detection simplifies installation and setup

ELEKTROGERÄTE RÜCKNAHME

## Commercial data

| | |
|---|---|
| Item number | 1085171 |
| Packing unit | 1 pc |

| | |
|---|---|
| Minimum order quantity | 1 pc |
| Sales key | DN20 |
| Weight per piece (excluding packing) | 260 g |
| Customs tariff number | 85176200 |
| Country of origin | TW |

# Technical data

## Dimensions

| | |
|---|---|
| Width | 22.5 mm |
| Height | 140.4 mm |
| Depth | 92.4 mm |

## Notes

| | |
|---|---|
| Note on application | Only for industrial use |
| Note on application | As things stand now, we are preparing the product so that, as of December 11, 2027, it will comply with the requirements of the EU Cyber Resilience Act (CRA) based on the information currently available regarding the CRA. |

Utilization restriction

| | |
|---|---|
| EMC note | EMC: class A product, see manufacturer's declaration in the download area |

## Material specifications

| | |
|---|---|
| Color (Housing) | gray (RAL 7042) |
| Color (Cover) | light gray (RAL 7035) |
| Housing material | Polycarbonate fiber reinforced |

## Mounting

| | |
|---|---|
| Mounting type | DIN rail mounting |

## Interfaces

Ethernet (RJ45)

| | |
|---|---|
| Number of interfaces | 5 |
| Connection method | RJ45 |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission speed | 10/100/1000 Mbps |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission length | 100 m (per segment) |
| Signal LEDs | Data receive, link status |
| No. of channels | 5 (RJ45 ports) |
| Input buffer | 1.5 Mbits |
| Output buffer | 1.5 Mbits |

Ethernet (SFP)

| | |
|---|---|
| Number of interfaces | 2 |
| Connection method | SFP |
| Transmission speed | 100/1000 Mbps (full duplex) |
| Transmission physics | Depending on the SFP module |
| Transmission length | up to 40 km (Depending on the fiber/SFP module used) |

| | |
|---|---|
| Signal LEDs | Data receive, link status |
| No. of channels | 2 (SFP ports) |

## Product properties

| | |
|---|---|
| Product type | Switch |
| Product family | Unmanaged Switch 1000 |
| MTTF | 59.2 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%) |
| | 872.1 Years (SN 29500 standard, temperature 25°C, operating cycle 21%) |
| | 836.5 Years (Telcordia standard, 25°C temperature, 21% operating cycle (5 days a week, 8 hours a day)) |
| Special properties | The product is being prepared for compliance with the Cyber Resilience Act (CRA) |

### Switch functions

| | |
|---|---|
| MAC address table | 4k |
| PROFINET conformance class | Conformance Class A |
| Status and diagnostic indicators | LEDs: $U_S$, link and activity per port |
| Basic functions | Unmanaged switch |
| | Autonegotiation |
| | Store and Forward switching mode |
| Additional functions | 100 BASE-TX/100BASE-FX (IEEE 802.3u) |
| | Jumbo frames (Max. 9,216 bytes) |
| | Quality of Service (QoS) prioritization (IEEE 802.1p) |
| | Energy-efficient Ethernet (IEEE 802.3az) |
| | Gigabit Ethernet 1000BASE-T (IEEE 802.3ab) |
| | 10Base-T (IEEE 802.3) |

## Electrical properties

| | |
|---|---|
| Maximum power dissipation for nominal condition | 4.635 W (at 24 V DC) |
| Transmission medium | Copper |

### Supply

| | |
|---|---|
| Supply voltage (DC) | 24 V DC |
| Supply voltage (AC) | 24 V AC (50/60 Hz) |
| Supply voltage range | 9 V DC ... 32 V DC |
| | 18 V AC ... 30 V AC (50/60 Hz) |
| Power supply connection | Via COMBICON, max. conductor cross-section 2.5 mm² |
| Residual ripple | 3.6 $V_{PP}$ (within the permitted voltage range) |
| Max. current consumption | 515 mA (at 9 V DC) |
| Typical current consumption | 30 mA (at 24 V DC) |
| Ground connection | Via DIN rail |

## Connection data

### Power supply

| | |
|---|---|
| Connection method | Push-in spring connection |
| pluggable | yes |
| Conductor cross-section, rigid | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section, flexible | 0.2 mm² ... 2.5 mm² |
| Conductor cross-section AWG | 24 ... 12 |
| Conductor cross-section, flexible, with ferrule, with plastic sleeve | 0.25 mm² ... 2.5 mm² |
| Conductor cross-section, flexible, with ferrule, without plastic sleeve | 0.25 mm² ... 2.5 mm² |
| | 0.25 mm² ... 2.5 mm² |
| Conductor cross-section, flexible, with ferrule, with plastic sleeve | 0.25 mm² ... 2.5 mm² |
| Stripping length | 10 mm |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP30 |
| Ambient temperature (operation) | -10 °C ... 60 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Altitude | 2000 m (maximum) |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Shock (operation) | 30g (EN 60068-2-27) |
| Vibration (operation) | in acc. with IEC 60068-2-6: 5g, 150 Hz |
| Air pressure (operation) | 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating) |
| Air pressure (storage/transport) | 79 kPa ... 108 kPa up to 2000 m above mean sea level (Without derating) |

## Approvals

### Conformity/Approvals

| | |
|---|---|
| UL, USA / Canada | UL 61010-1, UL 61010-2-201, UL 62368-1<br>Class I, Div. 2, Groups A, B, C, D, T4<br>Class I, Zone 2, Group IIC, T4 |
| FCC | Title 47 Part 15 Subpart B:2018 Class A |
| FCC certificate | T190905D11-C |

## EMC data

| | |
|---|---|
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Conformance with EMC directives | EN 61000-6-2 EN 61000-4-2 (ESD) Criterion B |
| | EN 61000-6-2 EN 61000-4-3 (electromagnetic fields) Criterion A |
| | EN 61000-6-2 EN 61000-4-4 (EFT burst) Criterion A |
| | EN 61000-6-2 EN 61000-4-5 (surge) Criterion B |
| | EN 61000-6-2 EN 61000-4-6 (line noise immunity) Criterion A |
| | EN 61000-6-2 EN 61000-4-8 (electromagnetic fields) Criterion A |
| | EN 61000-6-2 EN 55032 Class A |
| Noise immunity | EN 61000-6-2:2019 |

Noise emission

| | |
|---|---|
| Standards/regulations | EN_61000-6-4:2019 |

## Signaling

| | |
|---|---|
| Status display | LEDs: $U_S$, link and activity per port |

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-13.0 | 19170402 |
| ECLASS-15.0 | 19170402 |

### ETIM

| | |
|---|---|
| ETIM 10.0 | EC000734 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 43222600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 15(a), 7(a), 7(c)-I |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 22a0d945-4f18-4a9a-8c0e-ddc774a4478a |

EF3.1 Climate Change

| | |
|---|---|
| CO2e kg | 6.028 kg CO2e |

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com