HMC 11 120AC... A C1D2 TBUS



Data sheet
4278_en_A

© Phoenix Contact 2026-06-04

1 Description

HMC series supplemental circuit protector bused module.

Key features include:

- Toggle switch for quick break between line and load
- TBUS for external power supply
- ME MAX housing to withstand harsh environments
- Wide temperature range
- CID2 rated for hazardous locations
- Metal clip for easy connect to DIN rail
- AC disconnect for when power isolation is required

Observe these notes

Make sure you always use the latest documentation.
It can be downloaded at phoenixcontact.com/us-HMC.

This document is valid for the products listed in Section “Ordering data” on page 3.

Table of contents

1 Description 1
2 Ordering data 3
3 Technical data 3
4 Drawings 4

2 Ordering data

Products

Description	Type	Item No.	Max Total Current
HMC series of supplemental circuit protector bussed modules, 1A rating.	HMC 11 120AC 1A C1D2 TBUS	2907200	1 A
HMC series of supplemental circuit protector bussed modules, 2A rating.	HMC 11 120AC 2A C1D2 TBUS	2907201	2 A
HMC series of supplemental circuit protector bussed modules, 3A rating.	HMC 11 120AC 3A C1D2 TBUS	2907202	3 A
HMC series of supplemental circuit protector bussed modules, 5A rating.	HMC 11 120AC 5A C1D2 TBUS	2907203	5 A
HMC series of supplemental circuit protector bussed modules, 7.5A rating.	HMC 11 120AC 7.5A C1D2 TBUS	2907204	7.5 A
HMC series of supplemental circuit protector bussed modules, 10A rating.	HMC 11 120AC 10A C1D2 TBUS	2907205	10 A

3 Technical data

General data	
Max Operating Voltage	50 VDC / 120 VAC
Max Total Current (Connector)	See “Products” above
Max Total Current (TBUS)	15 A
SCCR Rating	1 kA
Ambient Temperature Range	-40°... 65°C
Mounting Position	Any
Clearances and Creepage Distances	UL 1077
Depending on:	Basic Insulation
Dimensions D/H/W	109.2 mm / 93.6 mm / 29.2 mm

Connection Data	
Connector	2x MSTBT 2,5/4-ST KMGY
Number of Positions	1 position
Connection Type	Screw terminal
Connection Data Solid mm^2/ Stranded mm^2 / AWG	0.2... 2.5 / 0.2... 2.5 / 24... 12

Approvals	
UL Recognized	UL 1077
Hazardous Location Rating	Class I, Division 2 (CID2)

4 Drawings

Figure 1 Schematic




Figure 2 PCB Layout

