

## DESCRIPTION

## PRODUCT COVERED:

USL, CNL - Programmable Controller, CPU modules with Touch Panel, FT1A-M12RA and -C12RA. Consists of the following modules:

## CPU Modules with Touch Panel :

STN Monochrome LCD Type, Models FT1A-M12RA-W, -M12RA-B, -M12RA-S.

TFT Color LCD Type, FT1A-C12RA-W, -C12RA-B, -C12RA-S.

## GENERAL:

These devices are a modular Programmable Controller with touch panel. The device is used with products which can be programmed through link to control system of product.

## RATINGS:

Module	Power Supply	Input	Output
FT1A-M12RA-*	24 V dc 9.2 W,	I0-I5 Pins: 24 V dc, 4.4mA/pt All Other Pins: 24 V dc, 0.3mA/pt	240 V ac, 10 A (RES), 30 Vdc, 10 A (RES)
FT1A-C12RA-*	24 V dc 9.2 W,	I0-I5 Pins: 24 V dc, 4.4mA/pt All Other Pins: 24 V dc, 0.3mA/pt	240 V ac, 10 A (RES), 30 Vdc, 10 A (RES)

## ENVIRONMENTAL RATINGS:

Max. Surrounding Air Temperature : 55°C

For Use on a Flat Surface of a Type 1 Enclosure."

USL indicates investigation to the U.S. National Standard, UL 508, Seventeenth Edition.

CNL indicates investigation to the Canadian National Standard, C22.2 No. 142, Ed. 1987.