

DECLARATION OF CONFORMITY

We, IDEC IZUMI CORPORATION
7-31, Nishimiyahara 1-chome
Yodogawa-ku, Osaka 532-8550
Japan



declare under our sole responsibility that the product:

Description: Φ 16 Miniature Control Units
Series Name: L6 Series
Model No.: Details are as per attached sheets

to which this declaration relates is in conformity with the EC Directive on the following standard(s) or other normative document(s).

Applicable EC Directive: Low Voltage Directive (73/23/EEC)

Applicable Standard(s) : EN 60 947-1: 1991

EN 60 947-5-1: 1991 (excluding chapters 8.2 and 5.2.2)

5th August, 1998 at Osaka, Japan

Takeshi Sono

Vice President, Sales

Takeshi Sono

(Form 2-03-03)

No. D2B016
1st July, 1997
Page 1 of 2

Nomenclature

L6 Series

LA 2 L - M 1 T 2 7 V R
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

① LASeries L6

② Bezel shape: 1 --- Round
2 --- Square
3 --- Rectangular
4 --- Rectangular with guard

③ Operator function:
B --- Non-illuminated pushbutton
L --- Illuminated pushbutton
S --- Selector
T --- Lever
F --- Illuminated selector
K --- Key lock

④ Function: M --- Momentary
A --- Alternate
2 --- 2-position maintained
21 --- 2-position spring return from top or right
22 --- 2-position spring return from bottom
3 --- 3-position maintained
31 --- 3-position spring return from top or right
32 --- 3-position spring return from bottom or left
33 --- 3-position 2-way spring return
None - Pilot light

⑤ Operator shape:
1 --- Flush
2 --- Extended
3 --- Mushroom
None - Lever, Selector, illuminated selector or keylock selector



No. D2B016
1st July, 1997
Page 2 of 2

- ⑥ Switch unit: T - - - - - With LA-T Series switch unit
C - - - - - With HA-C Series switch unit

⑦ Contact configuration:

- 0 - - - - - No contact
1 - - - - - 1C (Gold overlaid on silver contacts)
2 - - - - - 2C (Gold overlaid on silver contacts)
5 - - - - - 1C (Silver contacts)
6 - - - - - 2C (Silver contacts)



⑧ Applicable Lamp Type:

- 1 - - - - - LED lamp, lamp rating (operational voltage) 5Vdc
2 - - - - - LED lamp, lamp rating (operational voltage) 6Vdc
3 - - - - - LED lamp, lamp rating (operational voltage) 12Vdc
4 - - - - - LED lamp, lamp rating (operational voltage) 24Vdc
D - - - - - LED lamp, lamp rating (operational voltage) 28Vdc
5 - - - - - Incandescent lamp, lamp rating 6V ac/dc, operational voltage 5V ac/dc
6 - - - - - Incandescent lamp, lamp rating 14V ac/dc, operational voltage 12V ac/dc
7 - - - - - Incandescent lamp, lamp rating 28V ac/dc, operational voltage 24V ac/dc
None - - - Non-illuminated type operator

⑨ Terminal configuration:

- None - - - Solder/Tab terminal
V - - - - - PWB terminal

⑩ Lens color:

- B - - - - - Black
R - - - - - Red
G - - - - - Green
Y - - - - - Yellow
A - - - - - Amber
W - - - - - White
S - - - - - Blue