

DIN rail perforated - NS 35/ 7,5 PERF 1000MM - 1207651

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 1000 mm



Key Commercial Data

Packing unit	20 pc
Minimum order quantity	20 pc
Weight per Piece (excluding packing)	454.0 GRM
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Height	7.5 mm
Length	1000 mm
Width	35 mm

General

Material	Steel
Coating	Galvanized, passivated with a thick layer
Color	silver
Test standard	In acc. with EN 60715: 2001
Nominal current I_N	1920 A

Standards and Regulations

Test standard	In acc. with EN 60715: 2001
Connection in acc. with standard	IEC / EN

Classifications

eCl@ss

eCl@ss 4.0	23150301
------------	----------

DIN rail perforated - NS 35/ 7,5 PERF 1000MM - 1207651

Classifications

eCl@ss

eCl@ss 4.1	23150301
eCl@ss 5.0	27141143
eCl@ss 5.1	27141143
eCl@ss 6.0	27141143
eCl@ss 7.0	27141143
eCl@ss 8.0	27400602
eCl@ss 9.0	27400602

ETIM

ETIM 2.0	EC001285
ETIM 3.0	EC001285
ETIM 4.0	EC000212
ETIM 5.0	EC000212

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	39121708
UNSPSC 11	39121708
UNSPSC 12.01	39121708
UNSPSC 13.2	39121708

Drawings

DIN rail perforated - NS 35/ 7,5 PERF 1000MM - 1207651

Dimensional drawing

