

Protective covers - HC-B 16-SD-ML/FS - 1678318

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

HEAVYCON protective cover, type B16, for sleeve housing without single locking latch, with retaining cord, IP54





Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 151850
Weight per Piece (excluding packing)	67.36 g
Country of origin	Germany

Technical data

Dimensions

Diameter of retaining cord eyelet	30 mm
Ambient conditions	
Degree of protection	ID54

Degree of protection	IP54
Ambient temperature (operation)	-20 °C 100 °C

General

Туре	B16
	For sleeve housing without single locking latch
Material	РА
Seal material	NBR
Locking latch material	High-grade steel, handle: PA-GF
Flammability rating according to UL 94	НВ
Color	gray
Seal present	yes



Protective covers - HC-B 16-SD-ML/FS - 1678318

Technical data

General

Connection	Plastic protective cover for short-term protection
Standards and Regulations	
Flammability rating according to UL 94	НВ

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC002314

UNSPSC

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712
UNSPSC 12.01	39121712
UNSPSC 13.2	39121712

Approvals

Approvals

Approvals

EAC



Protective covers - HC-B 16-SD-ML/FS - 1678318

Approvals

Ex Approvals

Approvals submitted

Approval details

EAC

Drawings

Dimensional drawing

Dimensional drawing

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com

06/01/2016 Page 3 / 3